


FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 550/60 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA |
| VERSIÓN | DUAL BEAD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 158 A8/154 B |
| LI/SS FREE ROLLING | 171 A8/167 B |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 550 | RIM REC | AG 16.00 |
| OD (MM) | 1240 | ECE | E11-106R-004391 |
| SLR (MM) | 540 | PR | 20 |
| RC (MM) | 3725 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.30 | 3.40 | 3.50 |
|------------|------|------|------|
| 10 FR | 8315 | 8465 | 8610 |
| 20 FR | 7485 | 7615 | 7750 |
| 30 FR | 6655 | 6770 | 6890 |
| 40 FR | 5940 | 6045 | 6150 |
| 50 FR | 5345 | 5440 | 5450 |
| 10 DW | 5745 | 5850 | 5950 |
| 20 DW | 5170 | 5265 | 5355 |
| 30 DW | 4600 | 4680 | 4760 |
| 40 DW | 4105 | 4180 | 4250 |
| 50 DW | 3625 | 3685 | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.