

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>250/80 R 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	125 A8 ; 125 B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	250	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	835	<b>RIM ALT</b>	W 7; W 9
<b>SLR (MM)</b>	375	<b>ECE</b>	E11-106R-006605
<b>RC (MM)</b>	2539	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
<b>50</b>	580	680	780	875	975	1060	1175	1240	1355	1470	1570	1650
<b>40</b>	580	680	780	875	975	1060	1175	1240	1355	1470	1570	1650
<b>30</b>	620	730	835	940	1045	1135	1260	1330	1455	1580	1685	1770
<b>10 LT</b>	780	910	1045	1175	1310	1420	1575	1665	1820	1975	2105	2215
<b>10 HT</b>	620	730	835	940	1045	1135	1260	1330	1455	1580	1685	1770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.