


# AGRIMAX RT 765

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>520/70 R 38</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> |  RADIAL            |
| <b>MACHINERY</b>    | PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| <b>VERSION</b>      | SPECIAL   |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 150 D   |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94062317 | <b>RC (IN)</b> | 208.7           |
| <b>SW (IN)</b>  | 20.3     | <b>RIM REC</b> | W 16 L          |
| <b>OD (IN)</b>  | 68.9     | <b>RIM ALT</b> | W 15 L; W 18 L  |
| <b>SLR (IN)</b> | 31.2     | <b>ECE</b>     | E11-106R-005525 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 40        | 4070 | 4730 | 5400 | 6060 | 6720 | 7390 |
| 30        | 4280 | 4970 | 5670 | 6370 | 7070 | 7760 |
| 25        | 4450 | 5180 | 5910 | 6640 | 7360 | 8090 |
| 20        | 4680 | 5450 | 6210 | 6980 | 7740 | 8500 |
| 5 LT      | 5450 | 6340 | 7230 | 8120 | 9020 | 9900 |
| 5 HT      | 4680 | 5450 | 6210 | 6980 | 7740 | 8500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.