

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>480/70 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	149 D



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1580	<b>RIM ALT</b>	W 14 L; W 16 L
<b>SLR (MM)</b>	711	<b>ECE</b>	E11-106R-005524
<b>RC (MM)</b>	4772	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1530	1755	2015	2275	2535	2795	3055	3250
50	1610	1845	2120	2395	2665	2940	3215	3415
40	1675	1925	2210	2495	2780	3065	3350	3560
30	1760	2020	2320	2620	2920	3220	3520	3740
10 LT	2050	2355	2705	3050	3400	3750	4095	4355
10 HT	1760	2020	2320	2620	2920	3220	3520	3740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.