


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>400/80 R 28 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 A8 ; 146 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94039227	<b>RC (IN)</b>	159.4
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	53.2	<b>RIM ALT</b>	W 12 ; W 14 L
<b>SLR (IN)</b>	24.2	<b>ECE</b>	E4-106R-002401

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	3110	3840	4500	5220	5890	6610
30	3370	4170	4880	5680	6390	7190
25	3570	4410	5170	6010	6770	7610
20	3730	4610	5400	6270	7070	7940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.