


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 580/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	183 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94069408	<b>RC (IN)</b>	242.8
<b>SW (IN)</b>	23.9	<b>RIM REC</b>	DW20B
<b>OD (IN)</b>	81.0	<b>RIM ALT</b>	DW18B; MW20B
<b>SLR (IN)</b>	36.3	<b>ECE</b>	E11-106R-006444

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41
45	7550	8770	10010	11230	12470	13690	15100	15970	17550
<b>FROM 40 TO 25</b>	8300	9640	11000	12350	13700	15050	16590	17560	19300
20	8740	9840	11220	12600	13980	15350	16930	17910	19680
12	8630	10030	11440	12840	14250	15650	17260	18260	20060
5	9130	10610	12100	13580	15070	16560	18250	19310	21220
<b>UPTO 20 CYC</b>	9410	10950	12490	14020	15550	17080	18830	19930	21890
<b>UPTO 10 CYC</b>	11240	13070	14900	16730	18560	20390	22490	23790	26130
<b>UPTO 5 CYC</b>	12320	14320	16320	18330	20340	22340	24640	26070	28640
5 HT	8470	9840	11220	12600	13980	15350	16930	17910	19680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.