


# MULTIMAX MP 527

<b>TIRE SIZE</b>	<b>400/70 R 20 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	149 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	404	<b>RIM REC</b>	13
<b>OD (MM)</b>	1068	<b>RIM ALT</b>	12 SDC ; 13 SDC ; 14
<b>SLR (MM)</b>	494	<b>ECE</b>	E4-106R-002656
<b>RC (MM)</b>	3282	<b>SRI</b>	525

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1560	1855	2115	2405	2700	2895	3250	-	-
40	1560	1855	2115	2405	2700	2895	3250	-	-
30	1675	1985	2265	2580	2890	3100	3480	-	-
25	1735	2060	2350	2675	3000	3215	3610	-	-
10 CYC.	1905	2340	2755	3170	3610	3925	4440	4680	4875
STATIC	2920	3590	4225	4860	5535	6020	6805	7180	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.