


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/60 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	174 D



ABMESSUNGEN IS STANDARD

SW (MM)	715	RIM REC	DW 25 B
OD (MM)	2041	RIM ALT	DW 27 B
SLR (MM)	896	ECE	E11-106R-0011234
RC (MM)	6092	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6
70	3355	3905	4455	5005	5555	6100
FROM 65 TO 40	3685	4290	4895	5495	6100	6700
30	3760	4375	4990	5605	6220	6835
20	3835	4465	5090	5720	6345	6970
10	4055	4720	5385	6045	6710	7370
UPTO 30 CYC	4185	4870	5555	6240	6925	7605
UPTO 15 CYC	4995	5815	6630	7450	8265	9080
UPTO 10 CYC	5475	6370	7265	8160	9055	9950
10HT	3760	4375	4990	5605	6220	6835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.