


# FLOTATION 648

<b>TYRE SIZE</b>	<b>550/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	156 A8/152 B
<b>LI/SS FREE ROLLING</b>	169 A8/165 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94045327	<b>RC (IN)</b>	146.7
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	48.8	<b>ECE</b>	E4-106R-001565
<b>SLR (IN)</b>	21.3	<b>PR</b>	18

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	44	45	46
5 FR	17240	17580	17900
10 FR	15510	15820	16110
20 FR	13790	14060	14320
25 FR	12310	12550	12790
30 FR	11080	11300	11350
5 DW	11880	12110	12350
10 DW	10690	10900	11110
20 DW	9500	9690	9880
25 DW	8490	8650	8820
30 DW	7640	7790	7830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.