


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>750/65 R 26 CHO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COSECHADORA / COSECHADORA DE ALGODÓN
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 A8/B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94030668	<b>RC (IN)</b>	193.2
<b>SW (IN)</b>	30.1	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	64.4	<b>RIM ALT</b>	DW 23 B
<b>SLR (IN)</b>	28.1	<b>ECE</b>	E4-106R-000810

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35
30	6430	7360	9010	9700	10870	11680
25	6430	7360	9010	9700	10870	11680
20	6890	7890	9630	10390	11640	12510
10 CYC	10600	12150	14850	16000	17930	19280
5 CYC	11570	13260	16200	17460	19560	21030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.