


# AGRIMAX RT 765

	<b>280/70 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / TRAKTÖR / ÜZÜM HASAT MAKINESİ / BIÇERDÖVER / UYGULAMALI MAKİNE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	112 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94021895	<b>RC (IN)</b>	93.3
<b>SW (IN)</b>	11.1	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	31.4	<b>RIM ALT</b>	W 8 ; W 8 L ; W 10
<b>SLR (IN)</b>	14.0	<b>ECE</b>	E4-106R-000633

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1170	1330	1530	1730	1930	2130	2300	2470
25	1170	1330	1530	1730	1930	2130	2300	2470
20	1250	1430	1640	1850	2070	2280	2470	2650
5 LT	1570	1800	2060	2330	2590	2850	3090	3320
5 HT	1250	1430	1640	1850	2070	2280	2470	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.