

AW 702

| | |
|---------------------------|---|
| TIRE SIZE | 10.5/80 - 18 |
| UM | US STANDARD |
| CONSTRUCTION | ⊗ BIAS |
| MACHINERY | EMPACADORA DE HENO / MAQUINARIA AGRÍCOLA / REMOLQUE / COSECHADORA / MAQUINARIA AGRÍCOLA / REMOLQUE |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 140 A8 |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94061778 | RC (IN) | 102.1 |
| SW (IN) | 10.8 | RIM REC | W 9 |
| OD (IN) | 34.8 | RIM ALT | W 8; 9 |
| SLR (IN) | 15.6 | ECE | E11-106R-007039 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 84 |
|------------------|-----------|
| 5 FR | 7720 |
| 15 FR | 6560 |
| 20 FR | 6170 |
| 25 FR | 5510 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.