


# RIDEMAX IT 696

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>340/80 R 24 IND</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 140 A8 ; 135 D   |



## DIMENSIONS US STANDARD

|                 |          |                |                     |
|-----------------|----------|----------------|---------------------|
| <b>USA CODE</b> | 94033843 | <b>RC (IN)</b> | 135.6               |
| <b>SW (IN)</b>  | 13.5     | <b>RIM REC</b> | DW 11               |
| <b>OD (IN)</b>  | 45.4     | <b>RIM ALT</b> | W 10 ; W 12 ; DW 10 |
| <b>SLR (IN)</b> | 20.5     | <b>ECE</b>     | E4-106R-002293      |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17   | 23   | 29   | 35   | 41   | 46   |
|-----------|------|------|------|------|------|------|
| 40        | 2260 | 2790 | 3260 | 3790 | 4280 | 4810 |
| 30        | 2440 | 3010 | 3530 | 4090 | 4610 | 5180 |
| 25        | 2590 | 3200 | 3750 | 4350 | 4910 | 5510 |
| 20        | 2690 | 3330 | 3900 | 4530 | 5100 | 5730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.