


# AGRIMAX RT 657

<b>TYRE SIZE</b>	<b>540/65 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINEYARD HARVESTER / TRACTOR / HARVESTER
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	150 D ; 153 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	530	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1464	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	670	<b>ECE</b>	E4-106R-000651
<b>RC (MM)</b>	4403	<b>SRI</b>	700

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1610	1880	2115	2345	2580	2785	3085	3350
<b>50</b>	1690	1975	2220	2465	2715	2925	3240	3520
<b>40</b>	1755	2045	2300	2555	2815	3030	3360	3650
<b>30</b>	1855	2160	2430	2700	2970	3200	3550	3855
<b>10 LT</b>	2160	2515	2830	3145	3460	3730	4135	4490
<b>10 HT</b>	1855	2160	2430	2700	2970	3200	3550	3855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.