


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 280/85 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 115 A8/B |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 292 | RIM REC | W 10 |
| OD (MM) | 1086 | RIM ALT | W 9 |
| SLR (MM) | 492 | ECE | E4-106R-000611 |
| RC (MM) | 3224 | SRI | 525 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|-----|------|------|------|------|------|
| 50 | 670 | 780 | 890 | 1000 | 1110 | 1215 |
| 40 | 670 | 780 | 890 | 1000 | 1110 | 1215 |
| 30 | 720 | 840 | 955 | 1075 | 1190 | 1305 |
| 10 LT | 900 | 1045 | 1190 | 1340 | 1485 | 1630 |
| 10 HT | 720 | 840 | 955 | 1075 | 1190 | 1305 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.