


# AW 711

<b>TYRE SIZE</b>	<b>440/55 R 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENT MACHINERY / IMPLEMENTS
<b>VERSION</b>	STUBBLE RESISTANT
<b>TL/TT</b>	TL
<b>LI/SS</b>	159 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	410	<b>RIM REC</b>	14
<b>OD (MM)</b>	945	<b>RIM ALT</b>	13
<b>SLR (MM)</b>	432	<b>ECE</b>	E4-106R-001398
<b>RC (MM)</b>	2893	<b>SRI</b>	450

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
50	1315	1710	2100	2410	2800	3195	3415	3765	4115	4375
40	1315	1710	2100	2410	2800	3195	3415	3765	4115	4375
30	1470	1915	2355	2695	3140	3580	3825	4215	4610	4900
25	1565	2035	2505	2870	3335	3805	4065	4485	4900	5210
20	1655	2155	2650	3035	3530	4030	4305	4745	5185	5515
10	1840	2390	2940	3370	3920	4475	4780	5270	5760	6125

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.