


# RM 500

<b>TIRE SIZE</b>	<b>500/85 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTARE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	182 A8 ; 170 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94075522	<b>RC (IN)</b>	172.5
<b>SW (IN)</b>	20.5	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	57.5	<b>RIM ALT</b>	W 15 L
<b>SLR (IN)</b>	24.5	<b>ECE</b>	E11-106R-005991

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58
<b>25 FREE ROLLING</b>	7870	9560	11060	12740	14430	15550	17050	18740
<b>25 DRIVE WHEEL</b>	5560	6750	7800	8990	10180	10980	12040	13230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.