

# SKID POWER HD (A)

|                     |             |
|---------------------|-------------|
| <b>TIRE SIZE</b>    | 23X8.5 - 12 |
| <b>UM</b>           | IS STANDARD |
| <b>CONSTRUCTION</b> | ❖ BIAS      |
| <b>MACHINERY</b>    | SKID STEER  |
| <b>VERSION</b>      | IMPLEMENT   |
| <b>TIRE TYPE</b>    | TL          |
| <b>LI/SS</b>        | 87 A8       |



## DIMENSIONS IS STANDARD

|                 |      |                |                   |
|-----------------|------|----------------|-------------------|
| <b>SW (MM)</b>  | 215  | <b>RIM REC</b> | 7.00 I - 55       |
| <b>OD (MM)</b>  | 585  | <b>RIM ALT</b> | 7.00 I - 70; 7 JA |
| <b>SLR (MM)</b> | 271  | <b>ECE</b>     | E11-106R-003361   |
| <b>RC (MM)</b>  | 1764 | <b>PR</b>      | 6                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.40</b> |
| 40                | 545         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.