


AGRIMAX V-FLECTO



TIRE SIZE	VF 710/75 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	183 D

ABMESSUNGEN US STANDARD

USA-CODE	94066339	RC (IN)	242.2
SW (IN)	28.3	RIM REC	DW 24 B
OD (IN)	81.1	RIM ALT	DW 23 B; DW 25 B
SLR (IN)	35.6	ECE	E11-106R-006764

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	8770	10170	11580	13150	14560	15960	17550
FROM 40 TO 25	9640	11190	12730	14460	16000	17550	19290
20	9830	11410	12980	14750	16320	17890	19680
12	10030	11630	13240	15030	16640	18240	20060
5	10600	12300	14000	15910	17600	19300	21220
*UPTO 5 CYC WITH FRONT LOADER	13500	15660	17820	20240	22400	24560	27010
5 HT	9830	11410	12980	14750	16320	17890	19680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.