

# AW 909

<b>TIRE SIZE</b>	15.0/55 - 17
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	134 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	391	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	850	<b>RIM ALT</b>	13
<b>SLR (MM)</b>	377	<b>ECE</b>	E4-106R-001546
<b>RC (MM)</b>	2490	<b>PR</b>	10

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.60
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.