


# EARTHMAX SR 452

|              |  |
|--------------|--|
| TIRE SIZE    | 24.00 R 35   |
| UM           | IS STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | САМОСВАЛ С ЖЕСТКОЙ РАМОЙ   |
| VERSION      | CUT RESISTANT COMPOUND   |
| TIRE TYPE    | TL   |
| LI/SS        | 209 B  |



## РАЗМЕРЫ IS STANDARD

|          |           |             |    |
|----------|-----------|-------------|----|
| OD (MM)  | 2170      | TRA CODE    | E4 |
| SLR (MM) | 995       | STAR RATING | ★★ |
| RC (MM)  | 6729      |             |    |
| RIM REC  | 17.00/3.5 |             |    |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 14000 | 14500 | 15500 | 16000 | 16500 | 17000 | 17500 | 18000 | 18500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.