


# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>380/90 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 A8/B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94065479	<b>RC (IN)</b>	234.6
<b>SW (IN)</b>	15.4	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	76.9	<b>RIM ALT</b>	W 11 ; W 13
<b>SLR (IN)</b>	36.3	<b>ECE</b>	E11-106R-006446

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	4070	5260	6350	7040	7440	8130	8830	9420	9920	---
25	4070	5260	6350	7040	7440	8130	8830	9420	9920	---
20	4350	5630	6800	7540	7970	8710	9460	10090	10610	---
5	5890	7610	9180	10180	10760	11760	12760	13620	14340	14880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.