


# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 480/95 R 54</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94514953	<b>RC (IN)</b>	273.9
<b>SW (IN)</b>	20.0	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	90.6	<b>RIM ALT</b>	DW 15 L
<b>SLR (IN)</b>	40.7	<b>ECE</b>	E11-106R-0011499

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	26	29	32	35	46
45	9310	10440	11590	12720	13380	14030	14430	14840	16310
<b>FROM 40 TO 25</b>	10060	11290	12530	13760	14470	15170	15610	16050	17640
20	10270	11520	12780	14040	14760	15480	15930	16380	17990
12	10470	11740	13030	14310	15050	15790	16240	16700	18350
5	11070	12430	13780	15140	15920	16690	17180	17660	19400
<b>UPTO 10 CYC.</b>	13630	15300	16980	18660	19600	20560	21160	21750	23900
<b>UPTO 20 CYC.</b>	11420	12820	14220	15620	16430	17220	17730	18230	20020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.