


AGRIMAX FORTIS

| | |
|--------------|--|
| TIRE SIZE | 600/70 R 34 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 160 D ; 163 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 591 | RIM REC | DW 18 L |
| OD (MM) | 1704 | RIM ALT | DW 20 B ; W 18 L |
| SLR (MM) | 761 | ECE | E4-106R-001401 |
| RC (MM) | 5109 | SRI | 800 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 2160 | 2520 | 2835 | 3150 | 3465 | 3735 | 4140 | 4500 |
| 50 | 2270 | 2650 | 2980 | 3310 | 3640 | 3925 | 4350 | 4725 |
| 40 | 2340 | 2730 | 3075 | 3415 | 3755 | 4050 | 4485 | 4875 |
| 30 | 2485 | 2900 | 3265 | 3625 | 3985 | 4300 | 4765 | 5175 |
| 10 LT | 2895 | 3380 | 3800 | 4225 | 4645 | 5005 | 5550 | 6030 |
| 10 HT | 2485 | 2900 | 3265 | 3625 | 3985 | 4300 | 4765 | 5175 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.