


EARTHMAX SR 30

| | |
|---------------------|--|
| TIRE SIZE | 26.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | AUTOBASCULANTĂ RIGIDĂ / AUTOBASCULANTĂ RIGIDĂ / ÎNCĂRCĂTOR |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 193 B ; 202 A2 |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| USA CODE | 94028788 | RIM REC | 22.00/3.0 |
| OD (IN) | 68.6 | TRA CODE | E3/L3 |
| SLR (IN) | 30.2 | STAR RATING | ★★/★ |
| RC (IN) | 204.7 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58 | 62 | 65 | 69 | 73 | 76 |
|-----------|-------|-------|-------|-------|-------|-------|
| 30 | 20900 | 21500 | 22700 | 23400 | 24700 | 25400 |
| 5 | 28300 | 29100 | 30900 | 32000 | 33100 | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.