

# FS 216

|                     |                          |
|---------------------|--------------------------|
| <b>TIRE SIZE</b>    | 23.1 - 26                |
| <b>UM</b>           | IS STANDARD              |
| <b>CONSTRUCTION</b> | ⊠ BIAS                   |
| <b>MACHINERY</b>    | HOLZSCHLEPPER / RÜCKEZUG |
| <b>VERSION</b>      | STEEL BELTED             |
| <b>TIRE TYPE</b>    | TL                       |



## ABMESSUNGEN IS STANDARD

|                 |      |                 |                  |
|-----------------|------|-----------------|------------------|
| <b>SW (MM)</b>  | 587  | <b>RIM REC</b>  | DW 20 A; DW 20 B |
| <b>OD (MM)</b>  | 1615 | <b>ECE</b>      | E11-106R-003662  |
| <b>SLR (MM)</b> | 726  | <b>PR</b>       | 16               |
| <b>RC (MM)</b>  | 4780 | <b>TRA CODE</b> | LS2              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.80 | 2.40 |
|------------|------|------|
| 10         | 6300 | -    |
| 30         | -    | 4500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.