


# TRAC SUPER

<b>TYRE SIZE</b>	<b>440/50 R 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	135 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	441	<b>RIM REC</b>	14.00
<b>OD (MM)</b>	872	<b>RIM ALT</b>	13.00
<b>SLR (MM)</b>	395	<b>ECE</b>	E4-106R-000662
<b>RC (MM)</b>	2674	<b>SRI</b>	410

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6
65	955	960	1070	1265	1440	1635	1855	1985	2180
40	1300	1305	1455	1720	1960	2225	2525	2700	2965
30	1440	1450	1615	1915	2175	2475	2805	3000	3295
10	1720	1730	1925	2280	2595	2945	3340	3575	3925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.