DATA SHEET

PRINTED ON
22-04-2026

AIROMAX AM 27

TIRE SIZE	**445/80 R 25**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	GRU MOBILE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	170 F

DIMENSIONI US STANDARD

CODICE USA	94076291	**RIM REC**	14.00/1.5
OD (IN)	53.1	**RIM ALT**	14.00/1.3
SLR (IN)	24.8	**ECE**	E11-54R-0022144
RC (IN)	162.0		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	76	80	83	87	91	94	98	102
50	10500	11000	11400	11700	12000	12300	12800	13200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..