


# AW 702

<b>TIRE SIZE</b>	<b>13.0/65 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	144 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94009800	<b>RC (IN)</b>	102.7
<b>SW (IN)</b>	13.2	<b>RIM REC</b>	11.0
<b>OD (IN)</b>	35.0	<b>ECE</b>	E4-106R-001905
<b>SLR (IN)</b>	15.7	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	71
5 FR	8640
15 FR	7340
20 FR	6910
25 FR	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.