


AS 504

TIRE SIZE	16.0/70 - 20
UM	IS STANDARD
CONSTRUCTION	 BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	147 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	418	RIM REC	13
OD (MM)	1097	RIM ALT	12 SDC; 14; 13 SDC
SLR (MM)	487	ECE	E4-106R-001875
RC (MM)	3214	PR	10

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.50
10 FR	4305
25 FR	3660
30 FR	3445
40 FR	3075
10 DW	3050
25 DW	2595
30 DW	2440
40 DW	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.