

# FLOTATION 648

700/50 - 22.5

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALYA MAKINESI / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	HIGH SPEED
<b>TIRE TYPE</b>	TL
	158 B/154 E
	170 B/166 E



## UNDEFINED US STANDARD

<b>USA CODE</b>	94025596	<b>RC (IN)</b>	148.6
<b>SW (IN)</b>	27.6	<b>RIM REC</b>	24.00
<b>OD (IN)</b>	50.0	<b>ECE</b>	E11-106R-004555
<b>SLR (IN)</b>	21.7	<b>PR</b>	16

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29	32	35
5 FR	18580	19640	20680
10 FR	16720	17680	18610
20 FR	14860	15720	16540
25 FR	13270	14030	14770
30 FR	11950	12630	13230
45 FR	10480	11090	11680
5 DW	13180	13930	14660
10 DW	11860	12540	13190
20 DW	10540	11140	11730
25 DW	9410	9950	10470
30 DW	8480	8960	9370
45 DW	7440	7860	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.