


AGRIMAX RT 855

| | |
|---------------------|--|
| TYRE SIZE | 520/85 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 155 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-------------------|
| USA CODE | 94021802 | RC (IN) | 215.2 |
| SW (IN) | 20.3 | RIM REC | DW 16 L |
| OD (IN) | 72.8 | RIM ALT | DW 18 L ; DD 16 L |
| SLR (IN) | 32.0 | ECE | E4-106R-000601 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|-------|-------|
| 30 | 4780 | 5640 | 6420 | 7180 | 7860 | 8540 |
| 25 | 4780 | 5640 | 6420 | 7180 | 7860 | 8540 |
| 20 | 5130 | 6040 | 6870 | 7690 | 8420 | 9150 |
| 5 LT | 6420 | 7560 | 8600 | 9620 | 10540 | 11450 |
| 5 HT | 5130 | 6040 | 6870 | 7690 | 8420 | 9150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.