


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>215/65 R 14</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	90 A8 ; 90 B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	220	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	630	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	290	<b>ECE</b>	E11-106R-0010331
<b>RC (MM)</b>	1906	<b>SRI</b>	310

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
50	280	325	375	415	465	510	600
40	280	325	375	415	465	510	600
30	300	350	400	450	500	550	645
10 LT	375	435	500	560	620	685	805
10 HT	300	350	400	450	500	550	645

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.