

FLOTATION 558

TIRE SIZE	500/45 - 22.5
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / CISTERNA MÓVEL / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	136 A8/132 B
LI/SS FREE ROLLING	148 A8/144 B



DIMENSÕES US STANDARD

CÓDIGO USA	94006267	RC (IN)	124.7
SW (IN)	19.7	RIM REC	AG 16.00
OD (IN)	41.1	ECE	E4-106R-002307
SLR (IN)	18.5	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33	36	39
5 FR	8860	9290	9720
10 FR	7970	8370	8750
20 FR	7090	7430	7780
25 FR	6330	6640	6940
30 FR	5700	5970	6170
5 DW	6290	6600	6910
10 DW	5670	5940	6220
20 DW	5040	5280	5530
25 DW	4500	4720	4940
30 DW	4050	4240	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.