


FL 630 ULTRA

TIRE SIZE	710/50 R 26.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ÉPANDEUR / VÉHICULE CITERNE / REMORQUE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	170 D ; 181 A8



DIMENSIONS US STANDARD

CODE USA	94047284	RC (IN)	165.7
SW (IN)	28.6	RIM REC	AG 24.00
OD (IN)	54.4	RIM ALT	AG 20.00
SLR (IN)	23.6	ECE	E11-106R-006812

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	3860	4400	4940	6140	6990	8070	9150	10000	10960	12040
40	4230	4830	5420	6750	7670	8860	10050	10980	12040	13230
30	5130	5850	6570	8170	9290	10720	12170	13290	14570	16000
25	5820	6650	7460	9280	10550	12190	13820	15100	16560	18190
15	6690	7640	8580	10660	12120	14010	15880	17350	19020	20900
5	7630	8700	9700	12150	13810	15960	18100	19760	21670	23810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.