

AGRIMAX RT 855

TIRE SIZE	520/85 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	157 A8/B



DIMENSIONER US STANDARD

USA CODE	94021819	RC (IN)	227.6
SW (IN)	20.3	RIM REC	DW 16 L ; W 16 A ; DD 16
OD (IN)	76.8	RIM ALT	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
SLR (IN)	33.8	ECE	E4-106R-000792

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	5000	5820	6650	7460	8280	9100
25	5000	5820	6650	7460	8280	9100
20	5360	6240	7110	7990	8860	9730
5 LT	6710	7800	8910	10000	11100	12190
5 HT	5360	6240	7110	7990	8860	9730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.