

AS 504

TIRE SIZE	4.00 - 16
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	66 A8
LI/SS FREE ROLLING	78 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	110	RIM REC	3.00 D
OD (MM)	628	RIM ALT	2.50 C
SLR (MM)	296	ECE	E11-106R-005193
RC (MM)	1935	PR	4

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.80
10 FR	595
25 FR	505
30 FR	475
40 FR	425
10 DW	420
25 DW	355
30 DW	335
40 DW	300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.