

MULTIMAX MP 527

| | |
|---------------------|--|
| TIRE SIZE | 440/80 R 24 IND |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 161 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|---------------------------|
| USA CODE | 94052080 | RC (IN) | 156.9 |
| SW (IN) | 17.4 | RIM REC | DW 14 L |
| OD (IN) | 51.7 | RIM ALT | DW 13 ; DW 13 L ; DW 15 L |
| SLR (IN) | 23.7 | ECE | E4-106R-002657 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 35 | 41 | 46 | 51 | 58 | 61 | 64 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 4890 | 5820 | 6640 | 7550 | 8470 | 9080 | 10200 | - | - |
| 25 | 4890 | 5820 | 6640 | 7550 | 8470 | 9080 | 10200 | - | - |
| 20 | 5250 | 6230 | 7100 | 8080 | 9060 | 9720 | 10910 | - | - |
| 15 | 5430 | 6460 | 7360 | 8380 | 9400 | 10090 | 11320 | - | - |
| 5 CYC. | 5970 | 7350 | 8650 | 9950 | 11330 | 12320 | 13930 | 14690 | 15300 |
| STATIC | 9150 | 11260 | 13260 | 15260 | 17360 | 18890 | 21350 | 22520 | 23460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.