


# AW 715

<b>TYRE SIZE</b>	500/50 R 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IMPLEMENTS / IMPLEMENT MACHINERY
<b>VERSION</b>	STEEL BELTED
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	149 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94514939	<b>RC (IN)</b>	113.8
<b>SW (IN)</b>	19.8	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	37.0	<b>ECE</b>	E11-106R-0011505
<b>SLR (IN)</b>	17.0		

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	15	17	23	29	35	41	46	52	58	73
40	2370	2660	3230	3660	4230	4810	5300	5810	6380	7160
30	2880	3220	3910	4430	5130	5820	6430	7030	7730	8670
25	3230	3620	4390	4970	5750	6540	7220	7900	8670	9740
15	3740	4190	5100	5780	6680	7590	8380	9170	10090	11320
5	4270	4770	5810	6580	7620	8640	9550	10450	11490	12900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.