


# AGRIMAX FORTIS

<b>TIRE SIZE</b>	<b>600/70 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 D ; 163 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	591	<b>RIM REC</b>	DW 18 L
<b>OD (MM)</b>	1704	<b>RIM ALT</b>	DW 20 B ; W 18 L
<b>SLR (MM)</b>	761	<b>ECE</b>	E4-106R-001401
<b>RC (MM)</b>	5109	<b>SRI</b>	800

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2160	2520	2835	3150	3465	3735	4140	4500
50	2270	2650	2980	3310	3640	3925	4350	4725
40	2340	2730	3075	3415	3755	4050	4485	4875
30	2485	2900	3265	3625	3985	4300	4765	5175
10 LT	2895	3380	3800	4225	4645	5005	5550	6030
10 HT	2485	2900	3265	3625	3985	4300	4765	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.