

# EARTHMAX SR 31

<b>TIRE SIZE</b>	<b>20.5 R 25</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ПОГРУЗЧИК / БУЛЬДОЗЕР / ШАРНИРНО-СОЧЛЕНЕННЫЙ САМОСВАЛ / ПОГРУЗЧИК / БУЛЬДОЗЕР
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	177 B ; 186 A2



## РАЗМЕРЫ IS STANDARD

<b>OD (MM)</b>	1480	<b>TRA CODE</b>	E3/L3
<b>SLR (MM)</b>	663	<b>STAR RATING</b>	★★/★
<b>RC (MM)</b>	4449		
<b>RIM REC</b>	17.00/2.0		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	4.25	4.50	4.75	5.00	5.25
50	5800	6150	6500	6700	6900	7300
10	8000	8250	8750	9000	9500	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.