

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 500/50 - 17 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 137 A8/133 B |
| LI/SS FREE ROLLING | 149 A8/145 B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94039807 | RC (IN) | 108.3 |
| SW (IN) | 20.1 | RIM REC | 16.00 |
| OD (IN) | 37.2 | ECE | E4-106R-001885 |
| SLR (IN) | 16.4 | PR | 14 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 32 | 35 | 41 |
|-----------|------|------|-------|
| 5 FR | 8710 | 9170 | 10030 |
| 10 FR | 7840 | 8240 | 9030 |
| 20 FR | 6970 | 7330 | 8020 |
| 25 FR | 6220 | 6550 | 7160 |
| 30 FR | 5600 | 5900 | 6390 |
| 5 DW | 6160 | 6480 | 7100 |
| 10 DW | 5540 | 5830 | 6390 |
| 20 DW | 4930 | 5180 | 5680 |
| 25 DW | 4400 | 4630 | 5070 |
| 30 DW | 3960 | 4170 | 4540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.