

# TF 9090

|                     |                                     |
|---------------------|-------------------------------------|
|                     | <b>7.50 - 20</b>                    |
| <b>UM</b>           | IS STANDARD                         |
| <b>CONSTRUCTION</b> | ❖ BIAS                              |
| <b>MACHINERY</b>    | KÜÇÜK TRAKTÖR / TRAKTÖR /<br>RÖMÖRK |
| <b>VERSION</b>      | STANDARD                            |
| <b>TIRE TYPE</b>    | TT                                  |
|                     | 109 A6                              |



## UNDEFINED IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 205  | <b>RIM REC</b> | 5.50 F         |
| <b>OD (MM)</b>  | 915  | <b>RIM ALT</b> | 5.00 F         |
| <b>SLR (MM)</b> | 431  | <b>ECE</b>     | E4-106R-002710 |
| <b>RC (MM)</b>  | 2725 | <b>PR</b>      | 8              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.40</b> |
| 30                | 1030        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.