

# AS 504

<b>TIRE SIZE</b>	<b>400/50 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	109 A8
<b>LI/SS FREE ROLLING</b>	121 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94060092	<b>RC (IN)</b>	94.0
<b>SW (IN)</b>	15.6	<b>RIM REC</b>	13 LB
<b>OD (IN)</b>	31.1	<b>ECE</b>	E11-106R-005494
<b>SLR (IN)</b>	14.5		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>44</b>
<b>5 FR</b>	4480
<b>15 FR</b>	3800
<b>20 FR</b>	3580
<b>25 FR</b>	3200
<b>5 DW</b>	3170
<b>15 DW</b>	2700
<b>20 DW</b>	2550
<b>25 DW</b>	2270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.