


AS 504

TIRE SIZE	19.0/45 - 17
UM	US STANDARD
CONSTRUCTION	 BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	131 A8
LI/SS FREE ROLLING	144 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019137	RC (IN)	101.5
SW (IN)	18.3	RIM REC	16.00
OD (IN)	34.1	ECE	E4-106R-001814
SLR (IN)	15.3	PR	14

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	8640
15 FR	7340
20 FR	6910
25 FR	6170
5 DW	6020
15 DW	5110
20 DW	4820
25 DW	4300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.