

AGRIMAX TURF RT 333

| | |
|---------------------|--|
| TIRE SIZE | 280/70 R 18 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VENDIMIADORA / MAQUINA PARA LA RECOGIDA DE FRUTA / MINITRACTOR / TRACTOR / COSECHADORA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 114 A8 ; 114 B |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 289 | RIM REC | W 9 |
| OD (MM) | 840 | RIM ALT | W 8; W 10 |
| SLR (MM) | 390 | ECE | E11-106R-006473 |
| RC (MM) | 2550 | SRI | 400 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|-----|-----|-----|------|------|------|------|------|
| 50 | 555 | 640 | 735 | 830 | 925 | 1015 | 1110 | 1180 |
| 40 | 555 | 640 | 735 | 830 | 925 | 1015 | 1110 | 1180 |
| 30 | 595 | 685 | 785 | 890 | 990 | 1090 | 1190 | 1265 |
| 10 LT | 745 | 860 | 985 | 1110 | 1240 | 1365 | 1490 | 1585 |
| 10 HT | 595 | 695 | 785 | 890 | 990 | 1090 | 1190 | 1265 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.