

AGRIMAXFACTOR

TYRE SIZE	480/70 R 34
UM	US STANDARD
MACHINERY	TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	155 D ; 158 A8



DIMENSIONS US STANDARD

USA CODE	94071036	RIM REC	W 15 L
SW (IN)	18.9	RIM ALT	W 14 L ; W 16 L
OD (IN)	62.2	ECE	E11-106R-007643
SLR (IN)	28.7	TRA CODE	R1W
RC (IN)	187.4	TREAD DEPTH (32nd)	61.74

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
40	3340	3940	4530	5050	5640	6150	6760	7260	7950	8540
30	3510	4130	4760	5300	5930	6470	7100	7630	8360	8970
25	3660	4310	4960	5520	6180	6750	7400	7960	8710	9360
20	3840	4530	5210	5810	6490	7090	7770	8370	9150	9830
5 LT	4480	5270	6070	6770	7560	8260	9050	9740	10660	11450
5 HT	3840	4530	5210	5810	6490	7090	7770	8370	9150	9830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.