


# RT 853

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>520/85 R 38</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ<br>УБОРКИ ВИНОГРАДА / КОМБАЙН                                |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 155 A8/B   |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 516  | <b>RIM REC</b> | DW 16 L          |
| <b>OD (MM)</b>  | 1849 | <b>RIM ALT</b> | DW 18 L; DD 16 L |
| <b>SLR (MM)</b> | 830  | <b>ECE</b>     | E4-106R-001483   |
| <b>RC (MM)</b>  | 5592 | <b>SRI</b>     | 875              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 2135 | 2480 | 2830 | 3180 | 3530 | 3875 |
| 40         | 2135 | 2480 | 2830 | 3180 | 3530 | 3875 |
| 30         | 2285 | 2660 | 3030 | 3405 | 3780 | 4150 |
| 10 LT      | 2860 | 3325 | 3795 | 4260 | 4730 | 5195 |
| 10 HT      | 2285 | 2660 | 3030 | 3405 | 3780 | 4150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.