


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 710/60 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	715	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	2041	<b>RIM ALT</b>	DW 27 B
<b>SLR (MM)</b>	896	<b>ECE</b>	E11-106R-0010941
<b>RC (MM)</b>	6092	<b>SRI</b>	975

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6
70	3355	3905	4455	5005	5555	6100
<b>FROM 65 TO 40</b>	3685	4290	4895	5495	6100	6700
30	3760	4375	4990	5605	6220	6835
20	3835	4465	5090	5720	6345	6970
10	4055	4720	5385	6045	6710	7370
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	5160	6005	6850	7695	8540	9380
10HT	3760	4375	4990	5605	6220	6835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.