


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	<b>600/60 R 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKBIL / SLÄPVAGN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D

## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	605	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1495	<b>RIM ALT</b>	AG 18.00
<b>SLR (MM)</b>	681	<b>ECE</b>	E11-106R-007198
<b>RC (MM)</b>	4495	<b>SRI</b>	725

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2	2.4	2.8	3.2	3.6	4	4.5	5
70	2045	2250	2725	3020	3490	3965	4380	4795	5265	5620	5915
65	2245	2470	2990	3315	3835	4355	4810	5265	5785	6175	6500
50	2715	2990	3620	4015	4645	5270	5825	6375	7000	7475	7865
40	3050	3360	4070	4510	5220	5925	6545	7165	7870	8400	8840
30	3390	3730	4515	5010	5795	6580	7265	7955	8740	9325	9815
25	3545	3905	4725	5240	6060	6885	7600	8320	9145	9760	10270
10	4040	4450	5385	5970	6905	7840	8660	9480	10415	11115	11700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.